

# Justin's Performance Center 301 Serendipity Drive Millersville, MD 21108

# www.JPCracing.com E-Mail: Tech@jpcracing.com 866-JPC-RACE

JPC Racing Axle Back P/N: 001axleback

2011-2012 Axle back kit



#### \*\*\*WARNING\*\*\*

This document and the images within it are the copyrighted intellectual property of Justin's Performance Center. They may not be reproduced or distributed in anyway, including electronic duplication and publication, without the express written consent of Justin's Performance Center. By installing this product the end user is agreeing to hold Justin's Performance Center, its staff, and business associates (hereto referred as JPC) harmless from any and all damages that may result, both directly and/or indirectly, from the use and or installation of this product. JPC will not be held responsible for any damages whatsoever. This is a performance enhancing product, and it is understood that the user is aware of, and liable for, any damages that result from the use and or misuse of this product.

**NOTE:** This product should be installed by, or under the supervision of, a qualified performance automotive specialist. Failure to do so may result in major property damage, serious injury, and or death. Be sure to exercise caution when driving your vehicle. Safety must be your primary concern! Always obey posted traffic laws and limits. Drive within the limits of the law, the limits of safety, and the limits of your ability.

### **Parts Included**

- 1 JPC 36 x 16 x 16" Box
- 1 JPC Installation directions
- 2 JPC Racing Axle Back Mufflers
- 2 JPC OEM Style 2.75" SEC Ball Clamps

## **Installation Instructions**

- Raise and support vehicle, remember always use jack stands for safety
- Loosen Clamps that retain mufflers to "over axle" pipes
- Remove the fasteners for the muffler hangers from the body of the car.
- Remove mufflers from the undercarriage with hangers still attached.
- Loosen clamps from the stock "over axle" pipes at the H pipe connection.
- Remove hangers from stock mufflers and reinstall on new JPC mufflers in the same position they came off.
- Install new clamp on the JPC muffler.
- Install your JPC muffler by reinstalling the muffler hangers with the factory hardware.
- Align mufflers for best fit then tighten the over axle clamp.
- Equalize protrusion of the tips from under the car by sliding the over axle pipes in or out.
- Tighten the H pipe to over axle pipe clamp
- Check for leaks

# Thank You for purchasing your JPC Racing parts! www.JPCRACING.com 866-JPC-RACE Email: Tech@jpcracing.com